

Enclosure heaters



Accessories for climate control Page 454 Therm software Page 474

Supply includes:

- PTC heater
- Quick-connection terminal
- Assembly parts


Note:

- For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat.

- In order to prevent condensation on assemblies, a hygrostat is recommended to regulate heating.
- In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.
- The installation of heaters is generally advisable, in order to prevent condensation.

Approvals:

Available on the Internet



Continuous thermal output 10 – 150 W, without fan

Model No.	Packs of	3105.310	3105.320	3105.330	3105.340	3105.350	3105.360	3105.370	Page
Width (B) mm		45	45	64	64	64	90	90	
Height (H) mm		120	120	155	155	230	165	180	
Depth (T) mm		46	46	56	56	56	75	75	
Continuous thermal output at $T_u = 10^\circ\text{C}$ W		8 - 10	18 - 20	23 - 30	49 - 50	63 - 75	86 - 100	130 - 150	
Rated operating voltage V, ~, Hz		110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	110 - 240, 1~, 50/60	
Pre-fuse A		2	2	4	4	4	4	4	
Accessories									
Thermostat	1 pc(s).	3110.000	3110.000	3110.000	3110.000	3110.000	3110.000	3110.000	467
Thermostat with strain relief	1 pc(s).	3110.100	3110.100	3110.100	3110.100	3110.100	3110.100	3110.100	467
Hygrostat	1 pc(s).	3118.000	3118.000	3118.000	3118.000	3118.000	3118.000	3118.000	468
Hygrostat with strain relief	1 pc(s).	3118.100	3118.100	3118.100	3118.100	3118.100	3118.100	3118.100	468
Digital enclosure internal temperature display and thermostat	1 pc(s).	3114.200	3114.200	3114.200	3114.200	3114.200	3114.200	3114.200	466
Bottom-mounted adaptor	1 pc(s).	3110.200	3110.200	3110.200	3110.200	3110.200	3110.200	3110.200	469

Enclosure heaters



Accessories for climate control Page 454 Therm software Page 474

Supply includes:

- PTC heater with fan
- Quick-connection terminal
- Assembly parts


Note:

- For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat.

- In order to prevent condensation on assemblies, a hygrostat is recommended to regulate heating.
- In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.
- The installation of heaters is generally advisable, in order to prevent condensation.

Approvals:

Available on the Internet



Continuous thermal output 235 – 800 W, with fan

Model No.	Packs of	3105.410	3105.380	3105.420	3105.390	3105.430	3105.400	Page
Width (B) mm		103	103	103	103	103	103	
Height (H) mm		200	200	200	200	200	200	
Depth (T) mm		103	103	103	103	103	103	
Continuous thermal output at T_u = 10°C 50/60 Hz W		235 / 250	250 / 265	355 / 400	400 / 415	710 / 800	800 / 870	
Rated operating voltage V, ~, Hz		115, 1~, 50/60	230, 1~, 50/60	115, 1~, 50/60	230, 1~, 50/60	115, 1~, 50/60	230, 1~, 50/60	
Pre-fuse A		4	4	6	6	10	6	
Accessories								
Thermostat	1 pc(s).	3110.000	3110.000	3110.000	3110.000	3110.000	3110.000	467
Thermostat with strain relief	1 pc(s).	3110.100	3110.100	3110.100	3110.100	3110.100	3110.100	467
Hygrostat	1 pc(s).	3118.000	3118.000	3118.000	3118.000	3118.000	3118.000	468
Hygrostat with strain relief	1 pc(s).	3118.100	3118.100	3118.100	3118.100	3118.100	3118.100	468
Digital enclosure internal temperature display and thermostat	1 pc(s).	3114.200	3114.200	3114.200	3114.200	3114.200	3114.200	466
Bottom-mounted adaptor	1 pc(s).	3110.200	3110.200	3110.200	3110.200	3110.200	3110.200	469

Rittal – The System.

Faster – better – everywhere.

